

SENSAPHONE Monitoring Sensor

WSG30 Wireless Sensors

WSG Wireless Power Failure Sensor



Description

The WSG Wireless Power Failure sensor is designed to work exclusively with the Sensaphone WSG30. This sensor includes a built-in radio transmitter, two AA alkaline batteries and a wall plug in power supply. The sensor will detect a loss of power at the outlet where the power supply is attached. The two AA alkaline batteries will power the sensor and allow it to transmit alarm information in the event that 120VAC power fails.

Specifications

Package Contents
(1) WSG Wireless Dry Contact Sensor
(2) AA Alkaline batteries
(1) Mounting kit
(1) 120VAC 60Hz/5VDC Power Supply

Operating Temperature Range:
32° to 122°F (0° to 50°C)

Operating Humidity Range:
0–95%

Transmit Power Output:
100mW (20dBm)

Range:
Up to 300' (90m)

Power Requirements:
(2) AA Batteries / 5VDC Power Supply (Included)

Wireless Technology:
ISM 2.4GHz, 100 mW (20dBm)

Housing:
White plastic

Size:
3.1" x 3.8" x 1.1"
7.9cm x 9.8cm x 2.85cm

Compatibility:
WSG30

**Specifications subject to change without notice*

WSG Wireless Power Failure Sensor FGD-WSG30-PWR